

FITTING INSTRUCTIONS

Please read instruction carefully before fitting the seat, and refer to care instructions for maintenance.

Place the metal plates, washers, nut retainers and fixing nuts onto the fixing bolts. Flip the nut retainer into a vertical position and insert through the pan fixing holes as shown in the right diagram.

When inserted, gently shake the pan fixing bolts so that the nut retainer turns to a horizontal position.

Lift and hold the fixing plate, and tighten the fixing bolts by hand. Slightly adjust the fixing bolts to line up with the holes in the hinges, then tighten the fixing bolts by the spanner provided, and lock the hinges by fully tightening the grub screws in the hinges.

CARE INSTRUCTIONS

The toilet seat has been coated with a durable lacquer, but still needs to be treated with care.

- Surfaces should be cleaned regularly with a soft damp cloth and mild soap.
- Do not scrub or use abrasive cleaning materials.
- Do not use bleach or cleaners containing bleach.
- Polishing of the seat surfaces should not be needed, but a wax free polish is advised as this does not smear.
- As with all toilets seats: If you use bleaches and strong cleaners in the pan, do not leave the seat closed whilst the cleaner acts on the pan– the fumes from bleaches & cleaners may destroy and/or discolour the finish on the seat.
- **IMPORTANT!** Do not stand on the lid or toilet seat; this may cause damage to it.

INSTALLATION METHOD

