

## **AFTERCARE INSTRUCTIONS**

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting, even the non-scratch cleaners. **NOTE: Never use abrasive detergents or disinfectants or those containing alcohol, hydrochloric acid or phosphoric acid.**

Bristan recommend E-Cloth for cleaning all of our bathroom & kitchen products. Using just water, E-cloth gives a smear free, deep clean by breaking up and holding dirt, which normal cloths leave behind. Order through your Bristan stockist. (ORDER CODE: ECLOTH)



## **GUARANTEE**

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

**NOTE: The 5-year guarantee on the cartridge is invalidated if damaged by any waterborne debris.**

**All products must have access for servicing or replacement during the life of the product.**

In the interests of continuous product development we reserve the right to alter specification as necessary

## **PRODUCT CODE: PM SABAS C**

**PRODUCT IDENTIFICATION CODE LASER ETCHED ON PRODUCT**  
Installer please fill in code here \_\_\_\_\_.(Where applicable)

## **TELEPHONE HELPLINE: 0844 701 6273**

Bristan Group Limited  
Birch Coppice Business Park  
Dordon  
Tamworth  
Staffordshire  
B78 1SG  
UK  
A Masco Company  
Website: [www.bristan.com](http://www.bristan.com)  
Telephone: +44 (0) 844 701 6274  
Facsimile: +44 (0) 844 701 6275  
Email: [enquire@bristan.com](mailto:enquire@bristan.com)

# BRISTAN

## **Prism Side Action Basin Mixer (With Pop-up Waste)**

## **Fitting Instructions & Contents List**

**Please keep these instructions for future reference and request of replacement part**

## WATER PRESSURE

This mixer is suitable for use at all supply pressures. However for optimum use both the hot and cold supplies should be reasonably balanced.

If the fitting is installed at low pressure (tank fed), then the minimum distance from the outlet of the nozzle to the underside of the cold tank should be 2 metres to ensure adequate performance.

### Operating Pressures: Min 0.2 bar, Max 7.0 bar.

This mixer should be installed in compliance with the Water Regulations. Where the supplies are unbalanced, i.e. hot water from cylinder tank/cold from the mains, approved check valves must be fitted in the supply pipes.

For further details contact your Local Water Authority.

## INSTALLATION

1. Identify all components and check for completeness, particularly before commencing installation.
2. Fit the mixer body (6) to the basin using the plinth and washer (7) above the surface and the fixing kit (8) below.
3. Secure the inlet connections tail pipes (9), (**COLD is at the front and the HOT is at the back**), to the fitting **by hand only (DO NOT OVERTIGHTEN)**. Then connect the hot and cold supplies.
4. Fit the pop-up waste (12), with washer (13) below and washer (14) above the basin. It is recommended that a silicone sealant be applied to both sealing faces of the washers. The plug (15) height can be set by adjusting the horizontal rod (11) and pop-up rod connecting bracket, and the screw in the base of the plug (**DO NOT OVERTIGHTEN**).
5. Fully open the mixer in the mid position, letting it run for a few minutes to check all joints and connections for leaks.
6. See the back page for aftercare instructions.

## MAINTENANCE

### If the fitting begins to drip:

1. Turn off the water supply.
2. Remove the handle lever (1), unscrew the grub screw (2) and then pull off the rest of the handle (1). Unscrew the shroud (3) and then the cartridge retaining nut (4).
3. Remove cartridge (5) from the body (6).
4. Clean or replace cartridge, clean and grease seal and refit.

**Please Note: That there are locating pins on the bottom of the cartridge that fit in holes inside the tap, to ensure it is fitted the correct way round.**

5. Replace cartridge and head and turn on the water supply.
6. Contact our helpline if problems persists.

## CONTENTS

1. Handle
2. Grub Screw
3. Shroud
4. Cartridge Retaining Nut
5. Cartridge
6. Body
7. Plinth & Washer
8. Fixing Kit
9. Tail Pipes
10. Pop-up Rod
11. Horizontal Rod
12. Waste
13. Flat Washer
14. Conical Washer
15. Waste Plug

