TECHNICAL DATA SHEET

HERITAGE®

BATHROOMS

Ryde

Single Control Exposed Mini Valve with Fixed Kit

Product Specification

Product Codes & Finishes: SLCSINMIN 03 (Vintage Gold)

SLCSINMIN 01 (Chrome)

Product Type: Traditional
Construction: Brass

Valve Type: Thermostatic Cartridge

Supply: All plumbing systems, preferably balanced

Inlet Connections: 15mm Compression

Outlet Connections: G ½"

Working Pressures: Min 0.1 Bar, Max 5.0 Bar

Maximum Temperature: Pre-set at 41oC, adjustable

Dimensions for Fitting: 110-155 mm inlet centres



Chrome Pictured

Additional Information

- 5 Year Guarantee
- Chrome plated to BS EN 248
- · Flow and temperature are controlled sequentially
- · Instant shut down if the water supply fails to reduce risk of scalding
- Maintains a constant temperature within IoC regardless of the demand on water supply
- · Valve can be fed from the top, bottom or rear

980 123 184 115 110 - 155 (Centres)

Flow Rates (litres per minute)

System Pressure	0.1bar	0.2bar	0.5bar	Ibar	2bar	3bar	5bar
Open Outlet	1.64	2.32	3.67	5.2	7.35	9	11.62

Technical Advice: For further information please call 0844 701 8503

or email technical@heritagebathrooms.com

Guarantee: 5 Year Guarantee covering manufacturing faults.

Max. 6

Max. 8

Max. 10

Max. 13

> 13

www.europeanwaterlabel.eu





Heritage Bathrooms, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG Telephone: 0844 701 8501 Facsimile: 0844 701 8502

Web Site: www.heritagebathrooms.com Email: technical@heritagebathrooms.com