

CLEANING, SEALING & AFTERCARE

MATTSTONE IMPREGNATING SEALER TECHNICAL DATA SHEET

REF: LTP/12



SEAL
2

LTP MATTSTONE

Natural Finish Impregnating Sealer For interior & exterior use

Suitable for all types of natural and artificial stone, unglazed porcelain, sandstone, slate, marble, terracotta, quarry, brick & concrete.

A natural, matt finish impregnating sealer. Helps protect against staining. Strongly repels water, oil and grease. Allows surfaces to breathe.

Directions for use

For application and cleaning tools see LTP website.

Shake the bottle prior to use. Ensure surface to be treated is completely clean and dry. Apply with a soft cloth, brush or sealant applicator pad allowing at least two hours between coats. More absorbent floors may require further coats and on such floors the product should be generously applied. After one hour rub over the surface with a soft fluff free cloth or buffing machine to obtain a uniform finish and remove any excess sealer. This product will dry after about two hours, but will take a further three days to become fully resistant. **N.B.** The aim is to completely fill the substrate with sealer without over applying it. Do not apply in direct sunlight. The sealer will help to inhibit oil based stains but such spillages should be wiped up immediately. On rougher surfaced floors it may be prudent to use an appropriate surface sealer as well. Some surfaces may appear delicately enhanced once dry. **Use only in well ventilated areas. Do not breathe vapours.** Do not use in temperatures under 5°C or over 25°C. **FOLLOWING APPLICATION DO NOT ALLOW SURFACES TO GET WET AND KEEP DRY FOR A MINIMUM OF 3 DAYS.** Always test first on an inconspicuous area, prior to general application.

Coverage

Per 10m²

Lower porosity floors	- approximately 1-2 litres
Higher porosity floors	- approximately 3-4 litres

Aftercare

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash Spray. Every 3 – 4 years surfaces may require more intensive cleaning in which case use LTP Grimex. Surfaces may require a top up coat of sealer after intensive cleaning. Refer to LTP Grimex technical data sheet for more information.

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 4 years for un-opened containers.

Health, Safety & Environmental

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, n-butyl acetate

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Keep out of the reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours, spray. Use only outdoors or in a well-ventilated area. **IF SWALLOWED:** Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container to a hazardous or special waste collection point. Repeated exposure may cause skin dryness or cracking. UFI: Y7A0-30SW-200G-4A1U UN: 1300



DANGER



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN



2025