



FIX-KST is a single part pre-mixed cementitious dry mortar for the bonding and fixing of elements hard-foam. FIX-KST is rapid setting, frost resistant, waterproof and suitable for bonding on to most

common substrates including boarded wooden floors. It can be used both internally and externally.

Surface Preparation: The surface must be clean, firm, dry, free of dust, dirt, oil & grease. When adhering on to timber flooring, ensure that the substrate is firm, stable and treated with a suitable primer. All substrates should be rigid enough to withstand loads without deflection.

Mixing & Application: FIX-KST should be added slowly to clean water (5kg to approx. 1.0 litres). FIX-KST can either be applied by the 'dot and dab' method covering approximately 40% of the board up to a bed thickness of 35mm, or by the screeding method using an 8mm comb trowel. Do not mix in temperatures less than +5°C.

Conformity: Conforms to the requirements of EN12004 Class: C2FTS1

Open Time: Approx. 20 mins

Skin formation: After approx. 20 mins

Set Time: After approx. 3 - 4 hours (depending upon temperature & substrate)

Consumption: Depending on application thickness, approx. 5 -10kg/m²

Storage: Store in a cool, dry place and protect from excessive drafts.

Shelf Life: 6 months.

Quality Assurance: FIX-KST is manufactured in a plant certified with BS EN ISO 9001:ISO14001 and OHSAS 18001. Guaranteed against manufacturing defects only.



Health & Safety Warning

Contains Portland Cement

Labelled In Accordance With (EC) No. 1272/2008

Signal Word - Danger

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

P271 Use only outdoors or in well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

P501 Dispose of contents/container in accordance with local regulations.