

# Revive Zirconia Crushed Crystal Single Drop Cone Pendant Light DS-SE32101W0

INSTALLATION INSTRUCTIONS

V1.08.23

Please follow these care instructions to ensure your product retains it's high quality finish and please retain this leaflet for future reference.

## ENSURE THE DOMESTIC ELECTRICAL MAINS SUPPLY TO WHICH THE CEILING LIGHT IS BEING CONNECTED IS TURNED OFF!

- Position the ceiling light in a suitable location (according to the zonal diagram) ensuring that the domestic electrical mains supply is within reach of the electrical entry point of the product.
- 2. Carefully mark the position of the ceiling light mounting points using a soft pencil. Please ensure that all marked mounting points accurately match up with the fixing points on the ceiling light.
- 3. Before drilling, ensure there are no hidden cables or pipes behind the mounting points. Using a suitable drill bit, drill holes in the marked positions to a suitable depth.
- 4. Insert wall plugs level with the surface of the ceiling. NB. For plasterboard ceilings, specialist fixings should be purchased.
- 5. Line up product with marked fixing points, feed mains supply through the lights base and screw into place.
- 6. Connect the domestic mains supply to the terminal block according to the wiring diagram.
- 7. Switch the domestic electrical mains supply back on.



#### **Electrical Connection**



#### Maintenance & Cleaning

Caution - Always disconnect power supply when servicing or cleaning. • Use a clean dry soft cloth.

• Do not use abrasive cloths or polishes as this may cause damage to the product.

• Glass shades should only be washed with in lukewarm water and dried thoroughly before refitting



### **Safety Information**

We always recommend installation by a qualified electrician.

• This product is produced in conformity with all relevant safety regulations.

• To reduce the risk of fire, electrical shock, or personal injury, always turn off and unplug lamp and allow it to cool prior to replacing light bulb.

• Ensure the power is switched off from the mains before cleaning or carrying out maintenance.

• Do not attach your new light fixture wiring to any existing wiring that shows signs of wear and tear,

• When changing the bulb ensure that the power supply has been disconnected and the bulb has cooled down before replacing.